



ACCESS SOLUTIONS SUPPLIED SHAFT — OR — BUILDER SUPPLIED SHAFT  
 SAVES EVERYONE TIME AND MONEY AND CAN  
 BECOME PART OF THE BUILDING STRUCTURE  
 TO SUPPORT OTHER MEMBERS  
 (CRANED IN FROM ABOVE)

CENTRE OPENING DOOR  
 SAME SIDE EXIT / ENTRY

ELEVATOR TYPE	MOTOR ROOMLESS
RATED LOAD	320 Kg
N° OF PASSENGERS	4 PERSONS
DRIVE	DRUM DRIVE
SPEED (m/s)	0.25 m/s
DRIVE CONTROL	VF
ROPE SUSPENSION	1:1
GEAR RATIO	GEARLESS
LANDINGS	G,1
MAIN FLOOR	GROUND FLOOR
TRAVEL	T.B.C.
SHAFT HEIGHT	T.B.C.
PIT DEPTH	150mm
CAR SIZE	1100 WIDE x 1400 DEEP
CAR HEIGHT	2200 CLEAR
DOOR OPENING	2100 HIGH x 900 WIDE

**ACCESS**  
*Solutions*

86 Burwood Drive  
 Blackmans Bay  
 Tasmania 7052  
 PO BOX 161 Kingston  
 P. (03) 6229 2476  
 info@access-solutions.com.au  
 www.access-solutions.com.au