



ACCESS SOLUTIONS SUPPLIED SHAFT — OR — BUILDER SUPPLIED SHAFT
 SAVES EVERYONE TIME AND MONEY AND CAN
 BECOME PART OF THE BUILDING STRUCTURE
 TO SUPPORT OTHER MEMBERS
 (CRANED IN FROM ABOVE)

HINGED DOOR (LEFT)
 SAME SIDE EXIT / ENTRY

| | |
|------------------|-----------------------|
| ELEVATOR TYPE | MOTOR ROOMLESS |
| RATED LOAD | 320 Kg |
| Nº OF PASSENGERS | 4 PERSONS |
| DRIVE | DRUM DRIVE |
| SPEED (m/s) | 0.25 m/s |
| DRIVE CONTROL | VF |
| ROPE SUSPENSION | 1:1 |
| GEAR RATIO | GEARLESS |
| LANDINGS | G,1 |
| MAIN FLOOR | GROUND FLOOR |
| TRAVEL | T.B.C. |
| SHAFT HEIGHT | T.B.C. |
| PIT DEPTH | 150mm |
| CAR SIZE | 1100 WIDE x 1400 DEEP |
| CAR HEIGHT | 2200 CLEAR |
| DOOR OPENING | 2100 HIGH x 900 WIDE |



86 Burwood Drive
 Blackmans Bay
 Tasmania 7052
 PO BOX 161 Kingston
 P. (03) 6229 2476
 info@access-solutions.com.au
 www.access-solutions.com.au